

**Coloured joint fillers that
enhance the aesthetics of tiles
and remain with it forever.**

- Long lasting joint filler
- It's Self-curing
- Available in range of colours
- Enhances Decor



Product Description

weber.color fine is a polymer cementitious tile grout used internal and external application. it is suitable for grouting ceramic tiles, vitrified tiles, marbles, granites, mosaics and natural stone in walls and floors.

Key Features

- **weber.color fine** is recommended for use on tile joints of 1-6mm width
- Ensure 24 hours time interval for grouting after tile fixing
- Keep the grouted area free from dust particles for minimum 24 hours
- For best results, use spacers and keep a minimum 2mm joint between tiles
- If the tiles are highly porous, do a sample test to check for possible staining. To avoid this problem, mask the tiles before grouting

Note: for application on any other substrate please contact Saint Gobain Weber personnel for technical assistance.

TECHNICAL PARAMETERS#

Bulk Density	1.10 - 1.20 gm/cc
Pot Life	Upto 1 Hour
Time to walk on grouted floor	24 hours after grouting
Recommended tile joint width	1 to 6mm
Site temperautre at the time of application	Between + 5° Celsius and 35° Celsius
Setting Time	
a) Initial	60-120 minutes
b) Final	160-220 minutes
Compressive Strength @ 28 days	>16Mpa

Consumption

Consumption depends on tile size and joint width. for example, for a tile of 20 cm x 20 cm with a 2mm joint width, the coverage will approximately 0.2 kg/m².

Shelf Life:

One year from the date of manufacturing for unopened bags, stored in dry condition.

Directions for Use

Surface preparation

- Clean and remove any loose particles
- Make sure that the tiles joints are clean and saturated and excess water is removed from the joints before grouting



Application

- Gradually add approximately 2.5 parts of powder to 1 part of clean water (measured by volume) and mix it to a smooth, workable, stiff paste
- Do not attempt to extend the pot life by adding more water to the mix
- Mix using a slow speed mixer
- Completely fill the tile joints with the **weber.color fine** diagonally across the tile surfaces using a rubber grouting trowel or an appropriate tool
- Wait till **weber.color dewdrop** has started to set (30 to 45 mins)
- Remove excess grout using a sponge (45 to 60 mins)
- After drying about 3 hours clean the tiles using a dry cloth

Pack Size: 1/2 Kg, 1 kg, 20 kg

Colour: Refer shade card

Please refer the table below

Tile size in mm	200X300	300X300	450X450	600X600
Tile size in inches	8X12	12X12	18X18	24X24
Thickness in mm	6	7	8	9
Joint width	consumption in kg/sqm			
2 mm	0.15	0.1	0.08	0.069
3 mm	0.17	0.16	0.123	0.104
5 mm	0.28	0.26	0.204	0.173

Health & Safety: weber.color fine is non-toxic. Use of gloves and goggles is recommended. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, medical advice should be sought. Weber components are non flammable.

#Note: Pot life, open time and adjustability time varies depending on the service conditions viz temperature, humidity and wind factor.

#Note: These test values were obtained during our laboratory tests. Site mixes may show slight differences in performance due to methods of applications.

Disclaimer: Information on this datasheet is to be treated as guideline for usage. Users are advised to undertake a trial for product suitability prior to it's full scale usage. There is no express or implied guaranty/warranty for the results. The company is not liable for any consequential damages.

Marketed by: Saint-Gobain Weber, Div of SEPR Refractories India Ltd. **Regd Office:** 5th level, **Leela Business Park**, Andheri-kurla Road, Andheri (E), Mumbai-400 059, India.

Email: weber-india@saint-gobain.com | **Website:** www.weber.co.in